Plasma Spray





Conventional plasma spray, commonly referred to as atmospheric plasma spray (APS), is the most versatile method for applying thermal spray coatings. With the ability to control the many facets of the plasma spray process, you can not only spray a wide range of materials, from metallics to ceramics, but also onto

virtually any material. With minimal coating distortion, the plasma torch can apply coatings to both small and large parts nearly continuously. The high degree of melting and particle velocity yields higher deposit densities and bond strengths than both flame and electric arc, making plasma coatings perfect for protection and refinishing applications.

Easy online quote requests at www.thermach.com. Call (920) 779-4299. Email sales@thermach.com.





AT-1000 POWER SUPPLY



The AT-1000 Power Supply's amperage is closed-loop controlled by the console, which monitors the

voltage at the power supply and plasma torch.

AT-2000 ARC STARTER



The AT-2000 Arc Starter is a solid-state high frequency ignition unit powered by the console and requires

no adjustments to operate.

AT-3000 CONSOLE



Using AT-1200 Powder Feeders, the AT-3000 console commands the feeders and offers

closed-loop RPM feed rate control.

AT-4000 HEAT EXCH



The AT-4000 Heat Exchanger, a 10-ton refrigerated chiller, is activated by and feeds its alarms directly to the AT-3000 console.

AT-1200 POWDER FEEDER



Thermach Powder Feeders deliver accuracy and repeatability and are highly customizable. Whether your requirements include high pressures, increased capacities, remote controllers, or quick-change canisters,

Thermach Powder Feeders can be designed to meet your specs.

SG-100 PLASMA TORCH



The SG-100 is a robust and proven plasma torch with plenty of options. This multimode torch can spray

subsonic, Mach I, and Mach II depending on hardware. Available in standard, 90 degree, and interior diameter extension configurations.

Equipment that lasts. Precision parts that work.

Made in the USA for extreme conditions everywhere.

Solutions that allow your coatings to excel.

(920) 779-4299 (920) 779-4452 fax N677 Communication Drive Appleton WI 54914 USA

www.thermach.com